

SERIE 416.25 / SERIES 416.25

Series 416.25		Omologazioni / Approvals				
		EN 60252-1/A1  			 File E102953	
		Tensione / Voltage: 425 V ~ 10000 h cl. B 25/85/21 400 V ~ 10000 h cl. B 25/85/21 450 V ~ 3000 h cl. C 25/85/21 475 V ~ 3000 h cl. C 25/85/21 Classe di sicurezza / Safety protection class: S2			Valori omologati / Approved range: 1 ÷ 35 µF 40 ÷ 60 µF 40 ÷ 60 µF 1 ÷ 35 µF	
					Tensione / Voltage: 370 V ~ 60 Hz 10.000 AFC -25+70 °C Valori omologati / Approved range: from D.25 x H.60 to D.55 x H.122	
C(µF)	DxH (mm)	Codice / Part number 416.25.XX.KK	DxH (mm)	Codice / Part number 416.25.XX.KK	DxH (mm)	Codice / Part number 416.25.XX.KK
1	25x60	416.25.01.KK	30x53	416.25.A5.KK	35x53	416.25.A3.KK
1,5	25x60	416.25.02.KK	30x60	416.25.42.KK		
2	25x60	416.25.03.KK	30x60	416.25.41.KK	35x53	416.25.45.KK
2,5	25x60	416.25.04.KK	30x60	416.25.43.KK	35x53	416.25.46.KK
3	25x60	416.25.33.KK	30x60	416.25.44.KK	35x53	416.25.47.KK
3,15	30x53	416.25.99.KK	30x60	416.25.34.KK		
4	30x53	416.25.A1.KK	30x60	416.25.35.KK	35x53	416.25.48.KK
4,5	30x53	416.25.A2.KK	30x60	416.25.36.KK	25x72	416.25.63.KK
5	30x60	416.25.37.KK	25x72	416.25.64.KK	35x53	416.25.49.KK
6	30x60	416.25.38.KK			35x60	416.25.07.KK
6,3	35x60	416.25.08.KK	30x72	416.25.B8.KK		
7	35x60	416.25.09.KK	30x72	416.25.95.KK		
7,5	35x60	416.25.10.KK	30x72	416.25.96.KK		
8	35x60	416.25.11.KK	30x72	416.25.40.KK		
9	35x60	416.25.39.KK				
10	35x72	416.25.12.KK	35x60	416.25.C3.KK	40x72	416.25.A9.KK
12	35x72	416.25.72.KK				
12,5	35x72	416.25.13.KK				
13	35x72	416.25.14.KK				
13,5	35x77	416.25.81.KK	40x72	416.25.15.KK		
14	35x77	416.25.75.KK	40x72	416.25.16.KK		
15	40x72	416.25.17.KK	35x77	416.25.98.KK		
16	40x72	416.25.18.KK				
17,5	40x72	416.25.83.KK				
18	40x72	416.25.19.KK				
20	40x98	416.25.20.KK	40x77	416.25.B4.KK	35x98	416.25.90.KK
22	40x98	416.25.21.KK				
22,5	40x98	416.25.82.KK				
25	40x98	416.25.22.KK				
30	40x98	416.25.23.KK	45x98	416.25.84.KK		
31,5	45x98	416.25.24.KK	45x85	416.25.C7.KK		
35	45x98	416.25.25.KK				
40	45x122	416.25.26.KK	50x98	416.25.85.KK	45x98	416.25.C5.KK
45	45x122	416.25.27.KK	50x98	416.25.B3.KK		
50	45x122	416.25.28.KK	55x98	416.25.89.KK	50x98	416.25.A8.KK
55	50x122	416.25.29.KK				
60	50x122	416.25.30.KK	60x103	416.25.69.KK	55x98	416.25.A7.KK
65	55x122	416.25.31.KK				
70	55x122	416.25.32.KK				