

	1	2	3	4	5	6	7														
A					<p><b>Material</b> Zinc die-cast</p> <p><b>Delivery includes</b></p> <table> <tr> <td>1</td> <td>half-sheets</td> <td>(2x)</td> </tr> <tr> <td>2</td> <td>knurled screws</td> <td>(2x)</td> </tr> <tr> <td>3</td> <td>screw</td> <td>(1x)</td> </tr> <tr> <td>4</td> <td>half shells of strain relief</td> <td>(8x)</td> </tr> </table>		1	half-sheets	(2x)	2	knurled screws	(2x)	3	screw	(1x)	4	half shells of strain relief	(8x)	<p><b>SPECIFICATION MATERIAL Features</b></p> <p><b>Material and finish</b> Zinc-die-cast,nickel plated</p> <p><b>Temperature range</b> -40° to +120°</p> <p>④ <b>Cable diameter</b> 4.0mm - 13.0mm</p> <p><b>Attenuation factor</b> &gt;40 dB between 30Mhz and 1Ghz</p> <p><b>Requirements</b> VDE 0871,FCC 20780, 89/336/EU</p>		A
1	half-sheets	(2x)																			
2	knurled screws	(2x)																			
3	screw	(1x)																			
4	half shells of strain relief	(8x)																			
B									B												
C									C												
D									D												
E									E												
F									F												
G									G												
H									H												
	1	2	3	4	5	6	7														

					Date	Name	Title
				Drawn	18.12.04	Ken	AMET-25 RS
④	changed cable Ø	21.09.2015	A. Plate	Approved	25.09.08	W.Hellwig	
③	update of detailed specification. added sheets	28.02.2014	A. Siozios				Drawing-No.
②	Sheet 2 added	25.09.08	N.Schulz				Sheet rev04
①	drawing revised	04.07.07	N.Schulz				Sheet 3/5
	Modification	Date	Name				Replace

