



Nr. / No.	Farbe / Color	Länge / Length (m)	Gewicht / Weight (kg)
96196		0.3	0.019
96197		0.6	0.024
50960		1.8	0.053
68903		1.8	0.053
68975	TRANS	1.8	0.053
96198		1.8	0.053
50961		3.0	0.073
68904		3.0	0.073
68976	TRANS	3.0	0.073
96199		3.0	0.073
50962		5.0	0.121
68905		5.0	0.121
68977	TRANS	5.0	0.121
96288		5.0	0.121

USB 2.0 Hi-Speed Verlängerungskabel

- Verbinder: USB-A Stecker > USB-A Kupplung
- Innenleiter: 2xAWG24+2xAWG28 Kupfer
- Isolierung: PVC
- Schirmung: doppelt; AL-Folie + 16x5x0.1mm Geflecht
- USB Standard: High Speed USB 2.0
- Datenrate: max. 480Mbit/s
- RoHS-konform

USB 2.0 Hi-Speed extension cable

- USB-A plug > USB-B 90° angled plug
- Inner conductor: 2xAWG24 + 2xAWG28 Copper
- Insulation: PVC
- Shielding: double; AL foil + Braiding 16x5x0.1mm
- USB Standard: High Speed USB 2.0
- Data rate: max. 480Mbps
- RoHS compliant

Änderungen		Datum	Name	Bezeichnung	Blatt
Datum	Name	gez.: 03.06.2014	tf	USB Verl AA HiSpeed 2.0	von
		gepr.: 03.06.2014	tf		
		Norm:		Zeichnungs-Nr.: V1	
Änderungen vorbehalten / Subject to change					

