



Nr. / No.	Länge / length	Farbe / color
67189	0,2 m	
67999	0,5 m	
67185	0,5 m	
67890	1,0 m	
67188	1,0 m	
71221	2,0 m	

### USB 3.1 SuperSpeed+ Kabel

**Anschlüsse:** USB 3.1 Typ C-Stecker > USB 3.0 A-Stecker  
**Material:** Isolation: PVC; schwarz  
 Innenleiter: CU; AWG 28/32/34  
**max. Datenrate:** 5 Gbit/s  
**USB-Standard:** USB3.1/3.0,  
**Kompatibilität:** USB2.0, 1.1  
**Spannungsfestigkeit:** DC 300 V  
**Isolationswiderstand:** 10 MΩ  
**Kontaktwiderstand:** 2 Ω  
 RoHS-konform

### USB 3.1 SuperSpeed+ cable

**Connectors:** USB 3.1 Type C plug > USB 3.0 A plug  
**Material:** Insulation: PVC; black  
 Inner conductor: CU; AWG 28/32/34  
**max. data rate:** 5 Gbitps  
**USB standard:** USB3.1/3.0,  
**Compatibiliy:** USB2.0, 1.1  
**Dielectric strength:** DC 300 V  
**Insulation resistance:** 10 MΩ  
**Contact resistance:** 2 Ω  
 RoHS compliant

### Änderungen

Datum	Name	gez.:	Datum	Name
02.06.2016	jr	gez.:	31.01.2015	tf
		gepr.:	31.01.2015	tf
		Norm:		
Änderungen vorbehalten / Subject to change				

Bezeichnung	Blatt
USB 3.1 C/A 3.0	
Zeichnungs-Nr.:	von