



- DisplayPort Kabel; lose Ware
- 20 pol. Stecker > HDMI-Stecker
- DP-Stecker mit Verriegelung, vergoldet
- DP Version 1.2
- Auflösung: max. 4K x 2K @ 30 Hz
- Schirmung: Stanniol / AlMg-Legierungsdraht
- AWG 28
- RoHS konform

- DisplayPort cable; bulk
- 20 pin plug > HDMI plug
- DP connector with locking mechanism, gold-plated
- DP version 1.2
- Resolution: max. 4K x 2K @ 30 Hz
- Shielding: Tin foil / Al Mg alloy wire
- AWG 28
- RoHS compliant

Artikel-Nr. / Article No.	Beschreibung / Description	Länge X / Length X
51956	MMK 641-0100 G	1,0 m ± 30 mm / 1.0 m ± 30 mm
51957	MMK 641-0200 G	2,0 m ± 50 mm / 2.0 m ± 50 mm
51958	MMK 641-0300 G	3,0 m ± 70 mm / 3.0 m ± 70 mm
51959	MMK 641-0500 G	5,0 m ± 70 mm / 5.0 m ± 70 mm

**Änderungen**

Datum	Name	gez.:	Datum	Name
		gez.:	20.09.2017	ss
		gepr.:	20.09.2017	ss
		Norm:		
Änderungen vorbehalten / Subject to change				

Bezeichnung	<b>MMK 641-0200 G</b> <b>Schwarz / Black</b>	Blatt
Zeichnungs-Nr.:		von

