



- 1.CABLE:NO UL.,28AWG(7/0.127),TINNED AND STRANDED COPPER WIRE
INSULATOR:PVC,ID:0.85mm ,CABLING:9C+DRAIN WIRE
SHIELD:AL/MY COVERAGE
JACKET:PVC,COMPLIANCE ROHS,COLOR:BEIGE,D.D:5mm
- 2.PCS CONNECTOR:D-SUB 9 WAYS FEMALE SOLDER TYPE CONNECTOR
INSULATOR:P.B.T.+GLASS FIBER,COLOR:BLUE
CONTACT:COPPER ALLOY,GOLD FLASH OVER NICKEL PLATED
SHELL:NICKEL PLATED.
CONNECTOR COMPLIANCE ROHS
- 3.HOOD:PVC MOLDED TYPE WITH FOIL SHIELDED ON INNER
ON INNER MOLD AND INJECTION OUTER MOLD WITH
THUMB SCREW#4-40 UNC
COLOR:BEIGE,COMPLIANCE ROHS
- 4 Fulfill ROHS Guideline
- 5.ELECTRONIC TEST:100% OPEN SHORT+MISS WIRE TEST

PIN OUT

DB9PIN FEMALE(J1)	WIRE	DB9PIN FEMALE(J2)
1	=====	1
2	=====	2
3	=====	3
4	=====	4
5	=====	5
6	=====	6
7	=====	7
8	=====	8
9	=====	9
SHELL	DRAIN WIRE	SHELL

PART NO	CAB-09GG	SHEET NO	1	THIRD ANGLE PROJECTION SCALE N.T.S DRAWN BY & DATE SIZE A4 CHECKED BY & DATE UNIT <input checked="" type="checkbox"/> MM <input type="checkbox"/> INCH APPROVED BY & DATE
TITLE: DB9 PIN FEMALE TO DB9 PIN FEMALE BEIGE COLOR				
DWN NO D-CAB-09GG				