




3VE series molded case circuit breaker, using international advanced technology of circuit breaker. Meet IEC60947, VDE0660, such as the standard. Circuit breaker is suitable for ac voltage 660V, 50-60Hz frequency and rated current of 0.1-20A, AC 3 load circuit of the motor, power distribution lines or other electrical equipment, overload, short circuit protection.



Type	Rated current (A)	Hot time delay tripping current setting range(A)	Electromagnetic instantaneous trip current setting value(A)	Type	Rated current (A)	Hot time delay tripping current setting range(A)	Electromagnetic instantaneous trip current setting value(A)
3VE1	0.16	0.1-0.16	1.9	3VE3	1.6	1-1.6	19
	0.25	0.16-0.25	3		2.5	1.6-2.5	30
	0.40	0.25-0.4	4.8		4	2.5-4	48
	0.63	0.4-0.63	7.5		6.3	4-6.3	75
	1	0.63-1	12		10	6.3-10	120
	1.6	1-1.6	19.2		12.5	8-12.5	150
	2.5	1.6-2.5	30		16	10-16	192
	3.2	2-3.2	38		20	12.5-20	240
	4	2.5-4	48		25	16-26	300
	5	3.2-5	60		32	22-32	380
	6.3	4-6.3	75	3VE4 3VF1	10	6.3-10	120
	8	5-8	96		16	10-16	192
	10	6.3-10	120		25	16-25	300
	12	8-12.5	150		32	22-32	380
	16	10-16	192		40	28-40	480
	20	14-20	210		50	36-50	600
				63	45-63	700	