



REV.	DESCRIPTION	DRAWN	CHECKED	APPROVED
A	NEW RELEASE	LL 09/25/06'		

- NOTES:
- MATERIAL
 - INSULATOR:THERMOPLASTIC(UL 94V-0).
 - CONTACT: COPPER ALLOY.
 - SPECIFICATION
 - STORAGE TEMPERATURE:-40°C~+105°C.
 - CONTACT RESISTANCE:20mΩ max.(initial).
 - INSULATION RESISTANCE:1000MΩ min.
 - DIELECTRIC WITHSTANDING VOLTAGE:AC 500V PER MINUTE.
 - PART NUMBER: DS1012
 - PRODUCT NUMBER CODE:
 DS1012- X X X X X X X
 LOCK DIM.H
 8: 8.00mm (standard)
 4: 4.60mm (special)
 HOUSING COLOR
 A: GRAY
 B: BLACK
 CONTACT PLATING
 0: SELECTIVE GOLD FLASH
 STRAIN RELIEF
 N: W/O
 SCREW HOLE
 M: W/
 N: W/O
 EJECTOR TYPE
 L: Long
 No.OF CONTACTS
 10 14 16 24 26
 30 40 50 60 64
 SERIES No.
 DS1012

GENERAL TOLERANCE		ANGLE TOLERANCE		PROJECTION		TITLE	IDC SHROUDED HEADER
X.	±0.60	X.	±5°	UNITS	mm	MATES WITH PITCH 1.27mm FLAT CABLE	
.X	±0.38	.X	±3°	SHEET SIZE	A4	SERIES	DS1012 SERIES
.XX	±0.25	.XX	±2°	晨翔电子有限公司 CONNFLY® CONNFLY ELECTRONIC CO., LTD			
DRAWING TYPE		CUSTOMER					
SCALE	1:1	SHEET	1 OF 1				
DRAWING NO.		C-DS1012-XXXXXX					