



Installation tool for wire termination (included)

**Technical specification:**

Rated voltage: IEC 61076-2-104	3pos 60 V	4pos 30 V
Current rating: IEC 61076-2-104	4 A at 40°C with 0,5mm <sup>2</sup>	
Insulation resistance: IEC 60512	>= 100 MΩ	
Pollution degree: IEC 60664-1	3/2	
Degree of protection: IEC 60529	IP 67, in mated condition	
Temperature range: IEC 60664-1	-30°C ... +85°C	
Mating cycles: IEC 60512-9a	>= 100	
Wire cross section:	AWG 20 / max 0,5 mm <sup>2</sup>	

**Materials:**

Contact:	CuZn
Contact plating:	Au over Ni in mating area
Contact carrier:	PA6, UL 94
Cable sealing:	NBR
O-Ring:	Silicone / NBR
Coupling nut:	CuZn, Ni
Housing:	PA6 GF, UL 94

**Installation specification for locking nut to counter connector:**

Recommended torque:	0,4 Nm
Conec installation tool:	Torque wrench: 36-000200 Insert across flats 13: 36-000220

Part no:	Description:	Pos:	Cable-Ø:
42-00026	SAL - 8 - RKWC3-S	3	4 - 5,5mm
42-00028	SAL - 8 - RKWC4-S	4	4 - 5,5mm

DO NOT ALTER CAD DRAWING BY HAND Directive 2002/95/EC RoHS compliant	Index: b 06.12.11 K.H. Ä4175 font size adapted; dimension termination adapted; installation specif. adapted		<b>title</b> Female connector M8x1, field attachable, angled, screw termination  <b>dwg no:</b> 42K1A321  <b>part no:</b> see table						
	tolerance of cable:			<table border="1"> <tr> <td>drawn</td> <td>08.08.11</td> <td>Strakerjahn</td> </tr> <tr> <td>appd.</td> <td>16.09.11</td> <td>Hüther</td> </tr> </table>	drawn	08.08.11	Strakerjahn	appd.	16.09.11
	drawn	08.08.11		Strakerjahn					
	appd.	16.09.11		Hüther					
general tolerance: 0 ± 0,50mm 0,0 ± 0,25mm 0,00 ± 0,10mm									
THIS DRAWING MAY NOT BE COPIED OR REPRODUCED IN ANY WAY, AND MAY NOT BE PASSED ON TO A THIRD PARTY WITHOUT WRITTEN PERMISSION. OWNERSHIP AND COPYRIGHT OF CONEC GmbH									