


**Documents corresponding to the product:**

Standard EN 60947-1



Dimensions (mm)

H	W	L	W1	W2
32	40	35	26	45
H2	L1	L2		
48	6,5	37		

**AUXILIARY CONTACTS**

**5+2** standard +extended **7** YEAR TOTAL WARRANTY \*for industrial usage, 3 years warranty

**AUXILIARY CONTACTS**

At necessity the element provide auxiliary number of contacts. They are specially designed for mounting on the movable part of the magnetic core of the contactors LT 1K/D series.

**FUNCTIONS:**

- extending the number of the operative contactors up to 4 in different
- Combinations
  - switches on simultaneously with the other contact system of the contactor
- Operation class: AC 3

- insulation voltage: 690V
- Joining terminal: screw terminal
- Connecting:
  - flexible conductors with or without cable terminal
  - rigid conductors

**MOUNTING:**

- on the movable cover of the contactor through pinching
- mounting position: vertical gradient – maximum ± 5°
- Plastic: wear resistance of UV rays and non-flammable (self-extinguishing material)

Type	Number of contacts	Rated current	Section of the conductor (mm <sup>2</sup> )	Catalogue number
LT01-DN02	2NC	6A	0,5-1	<b>23002</b>
LT01-DN11	NO+NC	6A	0,5-1	<b>23011</b>
LT01-DN20	2NO	6A	0,5-1	<b>23020</b>
LT01-DN22	2NO+2NC	6A	0,5-1	<b>23022</b>
LT01-DN40	4NO	6A	0,5-1	<b>23040</b>
LT01-DN04	4NC	6A	0,5-1	<b>23004</b>
LT01-KN11	NO+NC	6A	0,5-1	<b>23001</b>
LT01-KN22	2NO+2NC	6A	0,5-1	<b>23003</b>



AUTOMATION



Dimensions (mm)

W1	W2	H	L	A
73	48	22	12,5	72

**AUXILIARY CONTACTS LT03-DN11**


**5+2** standard +extended **7** YEAR TOTAL WARRANTY \*for industrial usage, 3 years warranty

Providing on necessity additional number of plug points and are mounted sideward to the movable part of the magnetic cores of contactors of the series LT1 D. Variants with two additional plug points NO and NC are offered.

**FUNCTIONS:**

- expanding the number of the operational plug points
- switching on simultaneously with the rest of the contact system
- of the contactor

- flexible conductors with or without cable end
- solid conductors
- Mounting method:
  - mounting position – sideward to the contactor
- Plastic: resistant to UV and non-burning (self-extinguishing material)



**TECHNICAL CHARACTERISTICS:**

- Environment operational regime: AC 3
- Insulation voltage: 690V
- Double connector: screw connector
- Connection:

Type	Rated current	Section of the conductor (mm <sup>2</sup> )	Catalogue number
LT03-DN11	6A	0,5-1	<b>23311</b>



AUXILIARY CONTACT BLOCKS