


**Documents corresponding to the product:**

Standard EN 60309-1; EN 60309-2



**INDUSTRIAL PLUGS AND SOCKETS HT/HTN TYPE**



Made of special high quality plastic with alloys against aging at sun light exposing and for increasing the mechanical strength. They are designed in accordance with standard EN 60309 and provide reliable connection and high protection level against electrical current. They provide IP protection not less than IP 44/67. They are designed for surface or flush mounting, movable or fixed type.

**TECHNICAL DATA:**

- Rated voltage: 500V
- Rated short circuit current: according to the mounted protection in the boards
- Impulse voltage wear resistance: 8kV
- Mechanical wear resistance: 3000 cycles
- IP code: IP 44/67
- Plastic: UV rays wear resistance
- Ambient temperature: -5 to +65°C
- Altitude: up to 2000m
- Plugs and sockets: 6h



Model	In (A)	Poles	Un (V)	Dimensions (mm) A/B/C	IP code:	Packing/Box	Catalogue number
HT-013	16		230	121 / 84 / 53	44	2 / 10 / 100	<b>37013</b>
HT-023	32		230	138 / 92 / 63	44	2 / 10 / 60	<b>37023</b>



Model	In (A)	Poles	Un (V)	Dimensions (mm) A/B/C	IP code:	Packing/Box	Catalogue number
HT-014	16	3P+E	400	121 / 84 / 51	44	2 / 10 / 100	<b>37014</b>
HT-024	32		400	138 / 92 / 63	44	2 / 10 / 60	<b>37024</b>
HT-034	63	3P+E	400	230 / 109 / 36	44	2 / 10	<b>37034</b>
HT-044	125	3P+E	400	295 / 124 / 50	44	2 / 10	<b>37044</b>



Model	In (A)	Poles	Un (V)	Dimensions (mm) A/B/C	IP code:	Packing/Box	Catalogue number
HT-015	16	3P+N+E	400	129 / 92 / 62	44	2 / 10 / 60	<b>37015</b>
HT-025	32		400	149 / 97 / 70	44	2 / 10 / 60	<b>37025</b>
HT-035	63	3P+N+E	400	230 / 109 / 36	44	2 / 10	<b>37035</b>
HT-045	125	3P+N+E	400	295 / 124 / 50	44	2 / 10	<b>37045</b>

