

CAPACITIVE SENSORS – SERIES CM XX


3+0 standard +extended 3 YEAR TOTAL WARRANTY



EL-CM12

Capacitive sensors are used in machine systems and equipment for no-contact motion surveillance. They consist of two coaxial electrodes, a condenser and RC generator. This type of sensors reacts to both metal and non-metal objects, as the gearing distance for non-metal objects depends on their dielectric constants. They allow gearing distance adjustment for non-magnetic conductive materials. They are developed on the base of PNP and NPN transition. They have small dimensions and feature a metal cylindrical shell resistant to vibrations and a plastic lid which is oil and water resistant.

- Insulating resistance: $\geq 50 \text{ M } \Omega$
- Gearing distance: from 2 mm to 15 mm
- Precision of repetition: 0.01
- Ambient temperature: -25°C to $+65^{\circ}\text{C}$
- Gearing speed: 5mm/s
- Rated voltage: 6~36VDC; 90~230VAC
- IP code: IP 54



Type	Start distance (mm)	Power supply voltage	Type of transition	Type of contact	Output load	Packing / Box (pcs)	Catalogue number
EL-CM12-3004NA	0~4	15~30 VDC	NPN	NO	200 mA	1/100	46CM 12-32NA
EL-CM12-3004NB	0~4	15~30 VDC	NPN	NC	200 mA	1/100	46CM 12-32NB
EL-CM12-3004PA	0~4	15~30 VDC	PNP	NO	200 mA	1/100	46CM 12-32PA
EL-CM12-3004PB	0~4	15~30 VDC	PNP	NC	200 mA	1/100	46CM 12-32PB
EL-CM18-3008NA	0~8	15~30 VDC	NPN	NO	200 mA	1/100	46CM 18-38NA
EL-CM18-3008NB	0~8	15~30 VDC	NPN	NC	200 mA	1/100	46CM 18-38NB
EL-CM18-3008PA	0~8	15~30 VDC	PNP	NO	200 mA	1/100	46CM 18-38PA
EL-CM18-3008PB	0~8	15~30 VDC	PNP	NC	200 mA	1/100	46CM 18-38PB
EL-CM18-2008A	0~8	90~230VAC	SCR	NO	300 mA	1/100	46CM 18-28A
EL-CM24-3012NA	8	15~30 VDC	NPN	NO	200 mA	1/100	46CM 24-12NA
EL-CM24-3012NB	8	15~30 VDC	NPN	NC	200 mA	1/100	46CM 24-12NB
EL-CM24-3012PA	8	15~30 VDC	PNP	NO	200 mA	1/100	46CM 24-12PA
EL-CM24-3012PB	8	15~30 VDC	PNP	NC	200 mA	1/100	46CM 24-12PB
EL-CM24-2012A	8	90~230VAC	SCR	NO	300 mA	1/100	46CM 24-12A
EL-SM12-3110NA	10	15~30 VDC	NPN	NO	200 mA	2/200	46SM 12-31NA
EL-SM12-3110NB	10	15~30 VDC	NPN	NC	200 mA	2/200	46SM 12-31NB
EL-SM18-3110PA	10	15~30 VDC	PNP	NO	200 mA	1/100	46SM 18-31PA
EL-SM18-3110PB	10	15~30 VDC	PNP	NC	200 mA	1/100	46SM 18-31PB
EL-XM18-305PMI	5	15~30 VDC	inductive	NO	100 mA	1/100	46XM 18-35A
EL-XM18-305PMU	5	15~30 VDC	inductive	NC	100 mA	1/100	46XM 18-35B
EL-XM24-308PMI	8	15~30 VDC	inductive	NO	300 mA	1/100	46XM 24-38A
EL-XM24-308PMU	8	15~30 VDC	inductive	NC	300 mA	1/100	46XM 24-38B

Note: Sensor of Hall

Note: MI - current type; MU - voltage type



EL-CM18



EL-CM24



EL-SM12



EL-XM24