

Product Technical Data Sheet MANUFACTURER: AG Termopasty Grzegorz Gąsowski ul. Kolejowa 33 E, 18-218 Sokoty, phone 86 274 13 42

Kontakt PR

Special formulation for the regeneration of potentiometers that is ideal for the removal of any impurities depo sited throughout device operation. The product contains a special lubricant for correct slippage.

Application:

removal of sulphides and oxides, regeneration of potentiometers,

cleaning and preserving propertie.

Physicochemical properties of the liquid:

Parameters	UoM	Result
Relative density at 20°C	g/cm³	0,79
Viscosity	MPa∙s	22,8

Packagings:

Volume	Type of packaging	Collective packaging	Item Code
60 ml	aerosol	4 / 20	ART.AGT-007
300 ml	aerosol	12	ART.AGT-008
1 L	aerosol	1	ART.AGT-096

Warehousing:

Store in sealed containers in dry and well ventilated areas away from sources of heat and ignition and direct sunlight. Do not expose to temperatures exceeding 50°C/122°F. Protect against electrostatic discharge.

Data contained in this document are consistent with the current state of our knowledge. They describe typical product properties and applications. However, it is up to the user to examine the suitability of this product for specific applications. We deny liability for the obtained results on the grounds that application conditions lie beyond our control.

