

# Product Technical Data Sheet

## Silicone Oil

Viscous oil based on silicone reaching the most inaccessible places. It possesses high insulating properties, prevents from electrical discharges and effectively protects against moisture. It eliminates eddy-current generation and corona discharges; compatible with most of materials

### Application:

prevents from electrical discharges effectively protects against moisture.

### Physicochemical properties of the liquid:

Parameters	UoM	Result
Colour	-	colourless
Density	g/cm <sup>3</sup>	0,97
Viscosity	cSt	50

### Packagings:

Volume	Type of packaging	Collective packaging	Item Code
50 ml	plastic bottle with applicator	4 / 20	ART.AGT-014
100 ml	plastic bottle with applicator	4 / 20	ART.AGT-015
300 ml	aerosol	12	ART.AGT-016
1 L	plastic bottle	1	ART.AGT-100
5 L	plastic canister	1	ART.AGT-244

### Warehousing:

Store in tightly closed containers in a cool and dry place, away from heat sources and direct sunlight. Store at a temperature of 0-50°C. Do not store together with oxidising substances. Do not apply PVC packages.

Data contained in this document are consistent with the current state of our knowledge. They describe typical product properties and applications. However, it is up to the user to examine the suitability of this product for specific applications. We deny liability for the obtained results on the grounds that application conditions lie beyond our control.