

Product Technical Data Sheet

Vaseline Oil

The agent used to lubricate machine parts and precision mechanisms. Non-staining, odourless, colourless, neutral in contact with plastics. Reduces friction, preserves elements exposed to weather conditions, and protects against the adherences of plastic or rubber products to the mould. Consistency of the preparation allows for a wide range of applications.

Application:

the preparation reduces and limits friction, ideal for lubricating machinery and equipment, as well as any precision mechanisms, the oil effectively eliminates squeaks and scuffs, facilitates slipping, protects and preserves rubber and plastics.

Physicochemical properties of the liquid:

Parameters	UoM	Result
Colour	-	colourless
Density	g/cm ³	0,85 - 0,88
Viscosity	mPa*s	65 - 70

Packagings:

Volume	Type of packaging	Collective packaging	Item Code
50 ml	plastic bottle with applicator	4 / 20	ART.AGT-017
100 ml	plastic bottle with applicator	4 / 20	ART.AGT-018
300 ml	aerosol	12	ART.AGT-019
1 L	plastic bottle	1	ART.AGT-099
5 L	plastic canister	1	ART.AGT-245

Warehousing:

Store in tightly closed containers in a cool and dry place, away from heat sources and direct sunlight. Store at a temperature of 0-50°C. Do not store together with oxidising substances. Do not apply PVC packages.

Data contained in this document are consistent with the current state of our knowledge. They describe typical product properties and applications. However, it is up to the user to examine the suitability of this product for specific applications. We deny liability for the obtained results on the grounds that application conditions lie beyond our control.