

# Product Technical Data Sheet

## Kontakt S

Formulation for the purification of contacts from oxides and sulphides that protects against corrosion and ensures unobstructed current flow (especially in the case of oxidised and worn contacts). Used wherever clean contacts are required (inter alia: switches, sockets, plugs, integrated circuit sockets, bulb fixtures, fuse holders, contacts in capacitors). The agent does not react with the materials used in electronics.

### Application:

- restores low connector resistance,
- exerts cleaning properties,
- used in audio technology,
- protection against moisture and corrosion,
- prevents stray current formation.

### Physicochemical properties of the liquid:

Parameters	UoM	Result
Relative density at 20°C	g/cm <sup>3</sup>	0,74
Viscosity	MPa·s	20,5

### Packagings:

Volume	Type of packaging	Collective packaging	Item Code
60 ml	aerosol	4 / 20	ART.AGT-010
300 ml	aerosol	12	ART.AGT-009
400 ml	aerosol with brush	4 / 24	ART.AGT-227
1 L	metal bottle	1	ART.AGT-098

### Warehousing:

Store in sealed containers in dry and well ventilated areas away from sources of heat and ignition and direct sunlight. Do not expose to temperatures exceeding 50°C/122°F. Protect against electrostatic discharge.

Data contained in this document are consistent with the current state of our knowledge. They describe typical product properties and applications. However, it is up to the user to examine the suitability of this product for specific applications. We deny liability for the obtained results on the grounds that application conditions lie beyond our control.