

Product Technical Data Sheet

PRODUCENT: AG Termopasty Grzegorz Gąsowski
ul. Kolejowa 33 E, 18-218 Sokoly, tel. 86 274 13 42

Kontakt IPA plus

High-purity isopropyl alcohol "IPA". Perfectly removes all impurities from optical elements. Does not leave any marks or stains. Chemically neutral to commonly used materials. In a liquid and aerosol form.

Application:

CD-ROM drives, DVD drives,
audio-CD drives,
tool cleaning,
pcb tile cleaning,
flow meter cleaning,
photo CD devices,
screen cleaning,
AV heads and mechanisms,
ultrasonic cleaners,
fibre optic connectors.

Physicochemical properties:

| Parameters | U.o.M | Result |
|------------------------------|---------|--------|
| Main ingredient content | % | 99,9 |
| Relative density 20°C | g/ml | 0,785 |
| Acidity as acetic acid | % | 0 |
| Non-volatile residue | g/100ml | < 0 |
| Colour, Pt-Co | - | < 5 |
| Distillation IBP | °C | 82,2 |
| Distillation DP | °C | 82,4 |
| The refractive index at 20°C | - | 0,07 |
| UV absorption at 230 nm | - | 0,01 |
| UV absorption at 250 nm | - | 0,01 |
| UV absorption at 270 nm | - | < 0,01 |
| UV absorption at 290 nm | - | < 0,01 |
| UV absorption at 310 nm | - | < 0,01 |

Packagings:

| Volume | Type of packaging | Collective packaging | Item Code |
|--------|--------------------------------|----------------------|--------------|
| 50 ml | plastic bottle with applicator | 20 | ART.AGT-001 |
| 100 ml | plastic bottle with applicator | 20 | ART.AGT-002 |
| 250 ml | plastic bottle with atomizer | 12 | ART.AGT- 267 |
| 500 ml | plastic bottle | 8 | ART.AGT-105 |
| 500 ml | plastic bottle with sprinkler | 8 | ART.AGT-252 |
| 1 L | metal canister | 10 | ART.AGT-003 |
| 5 L | plastic canister | 1 | ART.AGT-004 |
| 5 L | metal canister | 1 | ART.AGT-218 |
| 20 L | plastic canister | 1 | ART.AGT-236 |
| 60 ml | aerosol | 4 / 20 | ART.AGT-005 |
| 300 ml | aerosol | 12 | ART.AGT-006 |
| 400 ml | aerosol with brush | 4 / 24 | ART.AGT-225 |
| 600 ml | aerosol | 12 | ART.AGT-202 |
| 250 ml | plastic bottle with sprinkler | 4 | ART.AGT-290 |

Warehousing:

Store in sealed containers in dry and well ventilated areas away from sources of heat and ignition and direct sunlight. Do not expose to temperatures exceeding 50°C/122°F. Protect against electrostatic discharge.

Data contained in this document are consistent with the current state of our knowledge. They describe typical product properties and applications. However, it is up to the user to examine the suitability of this product for specific applications. We deny liability for the obtained results on the grounds that application conditions lie beyond our control.