



UNIPOLAR DISTRIBUTION TERMINAL BLOCKS FOR COPPER AND ALUMINIUM CONDUCTORS

TECHNICAL DATA:

- Housing material: PA Nylon
- Terminal material: tin plated brass
- Grade of flame retardant: UL94v-0
- Mounting: DIN rail or screw fixing

Type	Current (A)	Quantity cross sections mm ²	Dimensions (mm)			Packing (pcs.)	Product category	Catalogue number
			L	H	W			
PPDTB80	80A	1x 6-16 mm ² 4x 2.5-6 mm ² 2x 2.5-16 mm ²	30	69	49	C	319080	
PPDTB125	125A	1x 10-35 mm ² 6x 2.5-16 mm ²	29	77	46	C	319125	
PPDTB160	160A	1x 10-70 mm ² 6x 2.5-16 mm ²	29	77	46	C	319160	
PPDTB250	255A	1x 35-120 mm ² 8x 2.5-16 mm ² 4x 2.5-10 mm ²	47	96	50	C	319250	
PPDTB400	400A	1x 95-185 mm ² 8x 2.5-16 mm ² 4x 2.5-10 mm ²	47	96	50	C	319400	



TERMINAL BLOCKS TBF TYPE

Type	Pieces in a terminal	Section of the conductor (mm ²)	Rated current (A)	Rated voltage (V)	Dimensions (mm)			Product category	Catalogue number
					L	H	W		
two terminal block	2	4 mm ²	32	400	12.4	14.5	20.5	C	31021
three terminal block	3	4 mm ²	32	400	17.0	14.5	20.5	C	31022
five terminal block	5	4 mm ²	32	400	26.6	14.5	20.5	C	31023

FAST LIGHTING CABLE CONNECTOR



Type	Pieces in a terminal	Section of the conductor (mm ²)	Rated current (A)	Rated voltage (V)	Dimensions (mm)			Product category	Catalogue number
					L	H	W		
lighting connector	3	1.0-2.5 mm ² /0.5-2.5 mm ²	25	400				C	31024