



■ UT210A



■ UT210B



■ UT210C

SPECIFICATIONS



Specifications	Range	Best Accuracy		
		UT210A	UT210B	UT210C
Model				
AC Current (A)	2A/20A/200A	±(2.5%+5)	±(2.5%+5)	
	20A/200A			±(1.8%+9)
AC Voltage(V)	2V/20V/200V/600V			±(1.0%+3)
DC Voltage(V)	200mV/2V/20V/200V/600V			±(0.7%+3)
Resistance(Ω)	200Ω/2kΩ/20kΩ/200kΩ/2MΩ/20MΩ			±(1.0%+2)
Capacitance (F)	20nF/200nF/2μF/20μF/200μF/2mF/20mF			±(4%+5)
Temperature(°C)	-40~1000°C			±(1%+3)
Temperature(°F)	-40~1832°F			±(1.5%+5)
Features				
Display Count		2000	2000	2000
Auto Range				✓
Jaw Capacity		17mm	17mm	17mm
True RMS			✓	✓
Diode	Around 3.0V			✓
NCV			✓	✓
Data Hold		✓	✓	✓
MAX/MIN			✓	✓
Relative Mode			✓	
LCD Backlight		✓	✓	✓
Auto Power Off	Around 15 Minutes	✓	✓	✓
Continuity Buzzer				✓
Low Battery Indication	≤2.5V	✓	✓	✓
Input Protection		✓	✓	✓
Input Impedance for DCV	≥10MΩ			✓

GENERAL CHARACTERISTICS

Power	AAA 1.5V x 2
LCD Size	39.3mm x 26.5 mm
Product Color	Red and Grey
Product Net Weight	UT210A/B - 160g UT210C - 170g
Product Size	UT210A/B - 155mm x 60mm x 33.5mm UT210C - 175mm x 60mm x 33.5mm
Standard Accessories	UT210A/B - Batteries UT210C - Batteries, Test Lead, Point Contact Temperature Probe
Standard Individual Packing	UT210A/B - Gift Box, English Manual UT210C - Gift Box, Carrying bag, English Manual
Standard Quantity Per Carton	40PCs
Standard Carton Measurement	UT210A/B - 345 x 245 x 300mm (0.025 CBM Per Standard Carton) UT210C - 385 x 345 x 305mm (0.041 CBM Per Standard Carton)
Standard Carton Gross Weight	UT210A/B - 9.5 kg UT210C - 11 kg



■ UT210D



■ UT210E


SPECIFICATIONS



Specifications	Range	Best Accuracy	
Model		UT210D	UT210E
AC Current (A)	20A/200A	±(2.5%+8)	
	2A/20A/100A		±(2.5%+5)
DC Current (A)	20A/200A	±(2%+3)	
	2A/20A/100A		±(2%+3)
AC Voltage(V)	2V/20V/200V/600V	±(1%+3)	±(1%+3)
DC Voltage(V)	200mV/2V/20V/200V/600V	±(0.7%+3)	±(0.7%+3)
Resistance(Ω)	10Hz/100Hz/1kHz/10kHz/60kHz	±(1%+2)	±(1%+2)
Frequency (Hz)	200Ω/2kΩ/20kΩ/200kΩ/2MΩ/20MΩ	±(0.1%+4)	
Capacitance (F)	2nF/20nF/200nF/2μF/20μF/200μF/2mF/20mF	±(4%+5)	±(4%+5)
Temperature(°C)	-40~1000°C	±(1%+3)	
Temperature(°F)	-40~1832°F	±(1.5%+5)	
Features			
Display Count		2000	2000
Auto Range		✓	✓
Jaw Capacity		17mm	17mm
True RMS		✓	✓
Diode	Around 3.0V	✓	✓
V.F.C		✓	✓
NCV		✓	✓
Data Hold		✓	✓
MAX/MIN		✓	✓
Zero		✓	✓
LCD Backlight		✓	✓
Auto Power Off	Around 15 Minutes	✓	✓
Continuity Buzzer		✓	✓
Low Battery Indication	≤2.5V	✓	✓
Input Protection		✓	✓
Input Impedance for DCV	≥10MΩ	✓	✓

GENERAL CHARACTERISTICS

Power	AAA 1.5V x 2
LCD Size	39.3mm x 26.5 mm
Product Color	Red and Grey
Product Net Weight	170g
Product Size	175mm x 60mm x 33.5mm
Standard Accessories	UT210D -Batteries, Test Lead, Point Contact Temperature Probe UT210E -Batteries, Test Lead
Standard Individual Packing	Gift Box, Carrying bag, English Manual
Standard Quantity Per Carton	40PCs
Standard Carton Measurement	385mm x 345mm x 305mm (0.041 CBM Per Standard Carton)
Standard Carton Gross Weight	11 kg



Intertek



■ UT211A



■ UT211B

SPECIFICATIONS



Specifications	Range	Best Accuracy	
Model		UT211A	UT211B
AC Current(A)	600mA/6000mA/60A	±(1.5%+10)	±(1.5%+10)
DC Current(A)	6000mA/60A		±(2%+3)
AC Voltage(V)	6V/60V/600V	±(0.8%+3)	±(0.8%+3)
DC Voltage(V)	600mV/6V/60V/600V	±(0.7%+3)	±(0.7%+3)
Resistance(Ω)	600Ω/6kΩ/60kΩ/600kΩ/6MΩ/60MΩ	±(0.8%+2)	±(0.8%+2)
Capacitance (F)	6.2nF~62mF	±(4%+5)	±(4%+5)
Features			
Display Count		6000	6000
Auto Range		✓	✓
True RMS		✓	✓
Diode	Around 3.0V	✓	✓
V.F.C.		✓	✓
NCV		✓	✓
Data Hold		✓	✓
Zero Mode			✓
Relative Mode		✓	
LCD Backlight		✓	✓
Auto Power Off	Around 15 Minutes	✓	✓
Continuity Buzzer		✓	✓
Low Battery Indication	≤2.5V	✓	✓
Input Protection		✓	✓
Input Impedance for DCV	≥10MΩ	✓	✓

GENERAL CHARACTERISTICS

Power	AAA 1.5V × 2
LCD Size	39.3mm × 26.5 mm
Product Color	Red and Grey
Product Net Weight	170 g
Product Size	175mm × 60mm × 33.5mm
Standard Accessories	Batteries, Test Lead
Standard Individual Packing	Gift Box, Carrying Bag, English Manual
Standard Quantity Per Carton	40 PCs
Standard Carton Measurement	385mm × 345mm × 305mm (0.041 CBM Per Standard Carton)
Standard Carton Gross Weight	11 kg



Intertek

V.F.C. NCV REL AUTO RANGE

TRUE RMS DATA HOLD

SPECIFICATIONS



■ UT213A



■ UT213B




■ UT213C

Specifications	Range	UT213A	UT213B	UT213C
Model				
AC Current (A)	4A/40A/400A 40A/400A	±(1.8%+9)	±(1.8%+9)	±(2.5%+5)
DC Current (A)	40A/400A			±(2.0%+3)
AC Voltage (V)	4V/40V/400V/600V	±(1.2%+5)	±(1.2%+5)	±(1.2%+5)
DC Voltage (V)	400mV/4V/40V/400V/600V	±(0.8%+1)	±(0.8%+1)	±(0.8%+1)
Resistance (Ω)	400Ω/4kΩ/40kΩ/400kΩ/ 4MΩ/40MΩ	±(1.0%+2)	±(1.0%+2)	±(1.0%+2)
Capacitance (F)	50nF/500nF/5μF/50μF/100μF 40nF/400nF/4μF/40μF/400μF /4mF/40mF	±(4.0%+5)	±(4.0%+5)	±(4.0%+5)
Frequency (Hz)	10Hz-1MHz	±(0.1%+4)	±(0.1%+4)	±(0.1%+4)
Temperature (°C)	-40 °C ~1000°C		±(1.0%+3)	±(1.0%+3)
Temperature (°F)	-40°F~1832°F		±(1.0%+6)	±(1.0%+6)
Features				
Display Count		4000	4000	4000
Auto Range		✓	✓	✓
Jaw Capacity		30mm	30mm	30mm
True RMS			✓	✓
Diode		Around 1.5V	Around 3.0V	Around 3.0V
NCV		✓	✓	✓
Data Hold		✓	✓	✓
Relative Mode		✓	✓	✓
MAX/MIN			✓	✓
LCD Backlight		✓	✓	✓
Flashlight		✓	✓	✓
Auto Power Off		✓	✓	✓
Continuity Buzzer		✓	✓	✓
Low Battery Indication	≤3.6V	✓	✓	✓
Input Protection		✓	✓	✓
Input Impedance for DCV	≥10MΩ	✓	✓	✓

GENERAL CHARACTERISTICS

Power	AAA 1.5V x 3
LCD Size	38mm x 24 mm
Product Color	Red and Grey
Product Net Weight	UT213A/B - 280g UT213C - 231.7g
Product Size	220mm x 75mm x 40mm
Standard Accessories	UT213A-Batteries, Test Lead UT213B/C-Batteries, Test Lead, Point Contact Temperature Probe
Standard Individual Packing	Gift Box, Carrying Bag, English Manual
Standard Quantity Per Carton	40 PCs
Standard Carton Measurement	485mm x 320mm x 385mm (0.060 CBM Per Standard Carton)
Standard Carton Gross Weight	UT213A/B - 23 kg UT213C - 20 kg



Intertek



■ UT216A



■ UT216B

SPECIFICATIONS



Specifications	Range	Best Accuracy	
Model		UT216A	UT216B
AC Current(A)	6A/60A/600A 60A/600A (50~400Hz)	±(2.5%+5)	±(2.5%+5)
AC Voltage(V)	6V/60V/600V/750V	±(1.2%+5)	±(1.2%+5)
DC Voltage(V)	600mV/6V/60V/600V/1000V	±(0.8%+1)	±(0.8%+1)
Resistance(Ω)	600Ω/6kΩ/60kΩ/600kΩ/6MΩ/60MΩ	±(1%+2)	±(1%+2)
Capacitance (F)	99.99nF/999.9nF/9.999μF/99.99μF/ 999.9μF/9.999mF/59.99mF	±(4.0%+5)	±(4.0%+5)
Frequency (Hz)	10Hz-1MHz		±(0.1%+4)
Features			
Display Count		6000	6000
Auto Range		√	√
Jaw Capacity		30mm	30mm
True RMS		√	√
Diode	Around 3.0V	√	√
V.F.C.			√
NCV		√	√
Data Hold		√	√
Relative Mode		√	√
MAX/MIN		√	√
LCD Backlight		√	√
Flashlight		√	√
Auto Power Off	Around 15 Minutes	√	√
Continuity Buzzer		√	√
Low Battery Indication	≤3.6V	√	√
Input Protection		√	√
Input Impedance for DCV	≥10MΩ	√	√

GENERAL CHARACTERISTICS

Power	AAA 1.5V × 3
LCD Size	38mm × 24 mm
Product Color	Red and Grey
Product Net Weight	UT216A - 280g UT216B - 231.7g
Product Size	220mm × 75mm × 40mm
Standard Accessories	Batteries, Test Lead
Standard Individual Packing	Gift Box, Carrying Bag, English Manual
Standard Quantity Per Carton	40 PCs
Standard Carton Measurement	485mm × 320mm × 385mm (0.065 CBM Per Standard Carton)
Standard Carton Gross Weight	UT216A - 19.8 kg UT216B - 18 kg



■ UT216C



■ UT216D


SPECIFICATIONS



Specifications	Range	Best Accuracy	
Model		UT216C	UT216D
AC Current(A)	60A/600A (50~400Hz)	±(2.5%+5)	±(2.5%+5)
DC Current(A)	60A/600A	±(2.5%+5)	±(2.5%+5)
AC Voltage(V)	6V/60V/600V/750V	±(1.2%+5)	±(1.2%+5)
DC Voltage(V)	600mV/6V/60V/600V/1000V	±(0.8%+1)	±(0.8%+3)
Resistance(Ω)	600Ω/6kΩ/60kΩ/600kΩ/6MΩ/60MΩ	±(1%+2)	±(1%+2)
Capacitance (F)	60nF/600nF/6μF/60μF/600μF/6mF/60mF	±(4.0%+5)	±(4.0%+5)
Frequency (Hz)	10Hz-1MHz	±(0.1%+4)	±(0.1%+4)
Temperature (°C)	-40 °C~1000°C	±(2.0%+5)	±(2.5%+3)
Temperature (°F)	-40 °F~1832°F	±(2.0%+10)	±(2.5%+6)
Features			
Display Count		6000	6000
Auto Range		✓	✓
Jaw Capacity		30mm	30mm
True RMS		✓	✓
Diode	Around 3.0V	✓	✓
V.F.C.		✓	✓
NCV		✓	✓
Data Hold		✓	✓
Zero Mode		✓	✓
Relative Mode		✓	✓
MAX/MIN		✓	✓
Inrush Current		✓	✓
LCD Backlight		✓	✓
OLED Display			✓
Analogue Bar Graph		61	21
Flashlight		✓	✓
Auto Power Off	Around 15 Minutes	✓	✓
Continuity Buzzer		✓	✓
Low Battery Indication	≤3.6V	✓	✓
Input Protection		✓	✓
Input Impedance for DCV	≥10MΩ	✓	✓

GENERAL CHARACTERISTICS

Power	AAA 1.5V × 3
LCD Size	38mm × 24 mm
Product Color	Red and Grey
Product Net Weight	231.7 g
Product Size	220mm × 75mm × 40mm
Standard Accessories	Batteries, Test Lead, Point Contact Temperature Probe
Standard Individual Packing	Gift Box, Carrying Bag, English Manual
Standard Quantity Per Carton	40 PCs
Standard Carton Measurement	485mm × 385mm × 385mm (0.065 CBM Per Standard Carton)
Standard Carton Gross Weight	20 kg



Intertek



■ UT201



■ UT202



■ UT202A


SPECIFICATIONS



Specifications	Range	Best Accuracy		
		UT201	UT202	UT202A
Model				
AC Current(A)	2A/20A/200A/400A 20A/200A/600A	±(1.5%+5)	±(1.5%+5)	±(1.5%+5)
AC Voltage(V)	2V/20V/200V/600V	±(1.2%+5)	±(1.2%+5)	±(1.2%+5)
DC Voltage(V)	200mV/2V/20V/200V/600V	±(0.8%+1)	±(0.8%+1)	±(0.8%+1)
Resistance(Ω)	200Ω/2kΩ/20kΩ/200kΩ/ 2MΩ/20MΩ	±(1%+2)	±(1%+2)	±(1%+2)
Temperature (°C)	-40°C~1000°C		±(1%+7)	
Temperature (°F)	-40°F~1832°F		±(1%+8)	
Features				
Display Count		2000	2000	2000
Auto Range		✓	✓	
Manual Range				✓
Jaw Capacity		28mm	28mm	28mm
Diode		✓	✓	✓
Auto Power Off		✓	✓	
Continuity Buzzer		✓	✓	✓
Low Battery Indication		✓	✓	✓
Data Hold		✓	✓	✓
MAX Mode		✓	✓	✓
MIN Mode				✓
Full Icon Display		✓	✓	
Input Impedance for DCV	Around 10MΩ	✓	✓	✓

GENERAL CHARACTERISTICS

Power	UT201/UT202-1.5V Batteries(R03) × 2,UT202A-9V Battery(6F22)
LCD Size	35.6mm × 18mm
Product Color	Red and Grey
Product Net Weight	220 g
Product Size	210mm × 75.6mm × 30mm
Standard Accessories	UT201/UT202A-Batteries, Test Lead UT202-Battery, Test Lead, Point Contact Temperature Probe
Standard Individual Packing	Gift Box, Carrying Bag, English Manual
Standard Quantity Per Carton	48 PCs
Standard Carton Measurement	503mm × 485mm × 295mm (0.072 CBM Per Standard Carton)
Standard Carton Gross Weight	24.8 kg



Intertek
UT203
UT204



■ UT203



■ UT204



■ UT204A


SPECIFICATIONS



Specifications	Range	Best Accuracy		
Model		UT203	UT204	UT204A
AC Current(A)	40A/400A 40A/600A	±(2.5%+5)	±(2.5%+5)	±(2.5%+5)
DC Current(A)	40A/400A 40A/600A	±(2%+3)	±(2%+3)	±(2%+5)
AC Voltage(V)	4V/40V/400V/600V	±(1%+5)	±(1%+5)	±(1%+5)
DC Voltage(V)	400mV/4V/40V/400V/600V	±(0.8%+1)	±(0.8%+1)	±(0.8%+1)
Resistance(Ω)	400Ω/4kΩ/40kΩ/400kΩ/ 4MΩ/40MΩ	±(1%+2)	±(1%+2)	±(1%+2)
Capacitance (F)	4nF/40nF/400nF/4μF/40μF /100μF			±(4%+3)
Frequency (Hz)	10Hz~10MHz	±(0.1%+3)	±(0.1%+3)	±(0.5%+3)
Temperature (°C)	-40 °C~1000°C			±(2.5%+3)
Features				
Display Count		4000	4000	4000
Auto Range		✓	✓	✓
Jaw Capacity		28mm	28mm	28mm
True RMS		✓	✓	
Duty Cycle	0.1%~99.9%	✓	✓	
Diode		✓	✓	✓
Auto Power Off		✓	✓	✓
Continuity Buzzer		✓	✓	✓
Low Battery Indication		✓	✓	✓
Data Hold		✓	✓	✓
Relative Mode		✓	✓	✓
Input Impedance for DCV	Around 10MΩ	✓	✓	✓

GENERAL CHARACTERISTICS

Power	9V Battery(6F22)
LCD Size	35.6mm × 18mm
Product Color	Red and Grey
Product Net Weight	260 g
Product Size	208mm × 76mm × 30 mm
Standard Accessories	UT203/UT204-Battery, Test Lead UT204A-Battery, Test Lead, Point Contact Temperature Probe
Standard Individual Packing	Gift Box, English Manual
Standard Quantity Per Carton	48 PCs
Standard Carton Measurement	503mm × 485mm × 295mm(0.072 CBM Per Standard Carton)
Standard Carton Gross Weight	58 kg



Intertek



■ UT205A



■ UT206A

SPECIFICATIONS



Specifications	Range	Best Accuracy	
		UT205A	UT206A
Model		UT205A	UT206A
AC Current(A)	400A/1000A	±(1.5%+5)	±(1.5%+5)
AC Voltage(V)	4V/40V/400V/600V	±(1.2%+5)	±(1.2%+5)
DC Voltage(V)	400mV/4V/40V/400V/600V	±(0.8%+1)	±(0.8%+1)
Resistance(Ω)	400Ω/4kΩ/40kΩ/400kΩ/4MΩ/40MΩ	±(1%+2)	±(1%+2)
Frequency (Hz)	10Hz~10MHz	±(0.1%+3)	±(0.1%+3)
Temperature (°C)	-40 °C~1000°C		±(2%+8)
Features			
Display Count		4000	4000
Auto Range		✓	✓
Jaw Capacity		40mm	40mm
Duty Cycle	0.1%~99.9%	✓	
Diode		✓	✓
Auto Power Off		✓	✓
Continuity Buzzer		✓	✓
Low Battery Indication		✓	✓
Data Hold		✓	✓
Relative Mode		✓	✓
LCD Backlight		✓	✓
Full Icon Display		✓	✓
Input Impedance for DCV	Around 10MΩ	✓	✓

GENERAL CHARACTERISTICS

Power	9V Battery(6F22)
LCD Size	37mm × 18mm
Product Color	Red and Grey
Product Net Weight	350 g
Product Size	236mm × 97mm × 40 mm
Standard Accessories	UT205A-Battery, Test Lead, Carrying Bag UT206A-Battery, Test Lead, Carrying Bag, Point Contact Temperature Probe
Standard Individual Packing	Gift Box, English Manual
Standard Quantity Per Carton	20 PCs
Standard Carton Measurement	525mm × 355mm × 380mm (0.071 CBM Per Standard Carton)
Standard Carton Gross Weight	15.7 kg



■ UT207



■ UT208



■ UT209

SPECIFICATIONS



Specifications	Range	Best Accuracy		
		UT207	UT208	UT209
Model				
AC Current(A)	66A/1000A	±(2%+8)	±(2%+8)	
	40A/1000A			±(2%+8)
DC Current(A)	66A/1000A	±(1.5%+8)	±(1.5%+8)	
	40A/1000A			±(1.5%+8)
AC Voltage(V)	6.6V/66V/600V	±(1.2%+5)	±(1.2%+5)	
	400mV/4V/40V/400V/600V			±(1.2%+5)
DC Voltage(V)	6.6V/66V/600V	±(0.8%+1)	±(0.8%+1)	
	400mV/4V/40V/400V/600V			±(0.8%+1)
Resistance(Ω)	600Ω/6.6kΩ/66kΩ/660kΩ/6.6MΩ/66MΩ	±(1%+2)	±(1%+2)	
	400Ω/4kΩ/40kΩ/400kΩ/4MΩ/40MΩ			±(1%+2)
Frequency (Hz)	660Hz/6.6kHz/66kHz/660kHz /6.6MHz/66MHz	±(0.1%+3)	±(0.1%+3)	
	4kHz/40kHz/400kHz/4MHz/40MHz			±(0.1%+3)
Temperature (°C)	-40 °C~1000°C		±(1%+3)	
Temperature (°F)	-40 °F~1832°F		±(1%+6)	
Features				
Display Count		6600	6600	4000
Auto Range		✓	✓	✓
Jaw Capacity		55mm	55mm	55mm
True RMS	AC Voltage	✓	✓	✓
Duty Cycle	0.1%~99.9%	✓	✓	
Diode		✓	✓	✓
Auto Power Off		✓	✓	✓
Continuity Buzzer		✓	✓	✓
Low Battery Indication		✓	✓	✓
Data Hold		✓	✓	✓
MAX/MIN		✓	✓	
Peak Max/Peak Min Mode				✓
LCD Backlight		✓	✓	✓
Analogue Bar Graph				41
Full Icon Display		✓	✓	✓
Inrush Current	AC Current	✓	✓	
Input Impedance for DCV	Around 10MΩ	✓	✓	✓

GENERAL CHARACTERISTICS

Power	9V Alkaline Battery(6LF22)
LCD Size	47mm × 30 mm
Product Color	Red and Grey
Product Net Weight	533 g
Product Size	286mm × 105mm × 45mm
Standard Accessories	UT207/UT209-Alkaline Battery, Test Lead
	UT208-Alkaline Battery, Test Lead, Point Contact Temperature Probe
Standard Individual Packing	Gift Box, Tool Box, English Manual
Standard Quantity Per Carton	5 PCs
Standard Carton Measurement	480mm × 372mm × 315mm (0.056 CBM Per Standard Carton)
Standard Carton Gross Weight	11 kg



■ UT207A



■ UT208A



■ UT209A

SPECIFICATIONS

AUTO RANGE

DUTY CYCLE

➔

DATA HOLD

TRUE RMS


⋯))

📄

Specifications	Range	Best Accuracy		
Model		UT207A	UT208A	UT209A
AC Current(A)	40A/400A/1000A	±(2%+2)	±(2%+2)	±(2%+2)
DC Current(A)	40A/400A/1000A	±(1.5%+5)	±(1.5%+5)	±(1.5%+5)
AC Voltage(V)	400mV/4V/40V/400V/750V	±(1.2%+3)	±(1.2%+3)	±(1.2%+3)
DC Voltage(V)	400mV/4V/40V/400V/1000V	±(0.8%+1)	±(0.8%+1)	±(0.8%+1)
Resistance(Ω)	400Ω/4kΩ/40kΩ/400kΩ/4MΩ/40MΩ	±(1%+2)	±(1%+2)	±(1%+2)
Capacitance (F)	4nF/40nF/400nF/4μF/40μF/100μF		±(4%+3)	
Frequency (Hz)	10Hz/100Hz/1kHz/10kHz/1MHz/10MHz	±(0.1%+3)	±(0.1%+3)	±(0.1%+3)
Temperature (°C)	-40°C~1000°C		±(2.5%+3)	
Features				
Display Count		4000	4000	4000
Auto Range		✓	✓	✓
Jaw Capacity		55mm	55mm	55mm
True RMS	AC Voltage/AC Current			✓
Duty Cycle	0.1%~99.9%	✓	✓	✓
Diode		✓	✓	✓
Auto Power Off		✓	✓	✓
Continuity Buzzer		✓	✓	✓
Low Battery Indication		✓	✓	✓
Data Hold		✓	✓	✓
LCD Backlight		✓	✓	✓
Input Impedance for DCV	Around 10MΩ	✓	✓	✓

GENERAL CHARACTERISTICS

Power	9V Alkaline Battery(6LF22)
LCD Size	47mm × 30 mm
Product Color	Red and Grey
Product Net Weight	533 g
Product Size	286mm × 105mm × 45mm
Standard Accessories	UT207A/UT209A-Battery, Test Lead UT208A-Battery, Test Lead, Point Contact Temperature Probe
Standard Individual Packing	Gift Box, Tool Box, English Manual
Standard Quantity Per Carton	20 PCs
Standard Carton Measurement	600mm × 370mm × 474mm (0.11 CBM Per Standard Carton)
Standard Carton Gross Weight	28.3 kg



Intertek



■ UT220



■ UT221



■ UT222

SPECIFICATIONS



Specifications	Range	Best Accuracy		
		UT220	UT221	UT222
Model				
AC Current(A)	200A/2000A	±(2.5%+5)		
	660A/2000A 600A/2500A		±(2.5%+5)	±(1.5%+5)
DC Current(A)	660A/2000A 600A/2500A		±(2.5%+5)	±(1.5%+5)
AC Voltage(V)	2V/20V/200V/1000V	±(1.2%+5)		
	6.6V/66V/660V/1000V 6V/60V/600V/1000V		±(1.2%+5)	±(1.0%+3)
DC Voltage(V)	2V/20V/200V/750V	±(0.8%+1)		
	6.6V/66V/660V/750V 6V/60V/600V/1000V		±(0.8%+1)	±(0.5%+2)
Resistance(Ω)	200Ω/2kΩ/20kΩ/200kΩ/2MΩ/20MΩ	±(1%+2)		
	660Ω/6.6kΩ/66kΩ/660kΩ/6.6MΩ/66MΩ 600Ω/6kΩ/60kΩ/600kΩ/6MΩ/60MΩ		±(1%+2)	±(1%+2)
Capacitance (F)	60nF/600nF/6μF/60μF/600μF/ 6000μF/60mF			±(3%+5)
Frequency (Hz)	66Hz/660Hz/6.6kHz/66kHz/660kHz /6.6MHz/20MHz		±(0.1%+3)	
	60Hz/600Hz/6kHz/60kHz/600kHz/ 6MHz/60MHz			±(0.1%+3)
Temperature (°C)	-40°C~1000°C			±(1.0%+10)
Temperature (°F)	-40°F~1832°F			±(1.0%+18)
Features				
Display Count		2000	6000	6000
Auto Range		✓	✓	✓
Jaw Opening		63mm	63mm	63mm
True RMS	AC Voltage/AC Current	✓	✓	✓
Duty Cycle	10%~90%		✓	✓
Diode		✓	✓	✓
Continuity Buzzer		✓	✓	✓
AC+DC				✓
Low-Pass Filtering			✓	✓
Inrush Current	AC Current		✓	✓
Relative Function			✓	✓
Data Hold		✓	✓	✓
MAX		✓		
MAX/MIN			✓	✓
Data Storage				1000
LCD Backlight		✓	✓	✓
Analogue Bar Graphic			66	61
Full Icon Display		✓	✓	✓
Auto Power Off		✓	✓	✓
Low Battery Indication		✓	✓	✓
Input Impedance	≥ 10MΩ	✓	✓	✓
I-OUT Function			✓	✓

GENERAL CHARACTERISTICS

Power	9V Alkaline Battery(6LF22)
LCD Size	43mm × 30 mm
Product Color	Red and Grey
Product Net Weight	UT220-390g, UT221/UT222-725g
Product Size	298mm × 100mm × 48mm
Standard Accessories	UT220- Test Leads UT221/222- Test Leads, Output Cable, Thermocouple(UT222)
Standard Individual Packing	UT220-Gift Box, Carrying Bag, English Manual UT221/UT222-Gift box, English Manual, Tool Box
Standard Quantity Per Carton	UT220-40PCs, UT221/UT222-5PCs
Standard Carton Measurement	UT220-645mm × 600mm × 330mm (0.128 CBM Per Standard Carton) UT221/UT222-510mm × 375mm × 320mm (0.061 CBM Per Standard Carton)
Standard Carton Gross Weight	UT220-30.2 kg, UT221/UT222-12 kg